



Gear Shield NC[®] Aerosol

Heavy Duty Lubricant

Product Data Sheet

Product Description

Gear Shield[®] NC Aerosol is a CFC free, heavy-duty lubricant that forms a tenacious lubricating film. **Gear Shield[®] NC Aerosol** is a high-viscosity base fluid combined with E.P. and oxidation –resistant additives further enhancing this protection. The aerosol packaging makes it ideal for lubricating gears, chains, cables, wire rope and sprockets in a variety of medium to heavy duty industrial applications. The **Gear Shield[®] NC Aerosol** is very convenient for re-lubricating gear teeth after inspection.

Features & Benefits

- High Viscosity fluid designed to lubricate heavily loaded open gears.
- Anti-wear and extreme pressure additives provide unparalleled protection.
- No build-up in gear tooth roots.
- Doesn't contain chlorinated solvents or lead.

Product Application

Gear Shield[®] NC Aerosol may be applied by spraying directly onto gearing after inspection.

Notes

Gear Shield[®] NC Aerosol is **Petron's Gear Shield[®] NC** packaged in an aerosol cans making a convient package for lubricating after inspections. **Petron's Gear Shield[®] NC** exceeds OEM and AGMA base oil viscosity requirements for open gear lubricants.

If you require further information contact Petron at: info@petroncorp.com



Gear Shield® NC Aerosol

Property	Method	Typical Data
----------	--------	--------------

*All Tests are performed before propellants are added.

Color	none	Black
Appearance	none	Viscous
Viscosity, cSt @ 40°C	ASTM D445	4,000 – 6,000
4 Ball Weld Load	ASTM D2596	400
FZG	A/2.76/sec/50°C	Pass 12

Testing listed is typical; no warranty is expressed or implied regarding results obtained from use. Information contained on this Product Data Sheet is subject to change without notification. Before using product name, always be sure to read and follow precautions and directions for use appearing on the product container. Seller shall not be liable for any loss or damage.